

Ceramic ventilated facades

The ceramic tiles are produced from mixture of natural materials, consisting of silica sands, crushed granite and natural clays.

1) COLOR

The color range of sintered ceramics is very wide and can satisfy all architectural visions. For a better imagination, we offer consultations directly in our office, where the client can see in detail your selected samples.

2) FORMATS

- 300 x 600 mm (thickness 9,5 mm)
- 600 x 600 mm (thickness 10,5 mm)
- 450 x 900 mm (thickness 10,5 mm)
- 600 x 1200 mm (thickness 10,5 mm)

Large-format tiling:

- 3600 x 1200 mm (thickness 3 6 mm)
- 3200 x 1600 mm (thickness 3 6 mm)
- 3000 x 1000 mm (thickness 3 6 mm)
- 3050 x 1350 mm (thickness 14,5 mm)

3) SURFACE

- Polished
- Satin

- Matt
- Roughened surface

Ceramic cladding tiles are frost -resistant with water absorption less than 3 %

4) WAY OF FIXING AND DETAILS

The mounting of the ceramic tiles is done either by invisible mechanical fixing or by gluing. Ultrathin tiles (thickness 3 - 6 mm) is possible to install only by gluing.

5) FLAMMABILITY

According to CSN 73 0810/ 2016: A1

For more information contact Triangel company.

Triangel spol. s r.o. Černokostelecká 2085/24 100 00 Praha 10 Czech Republic IČO: 65410777, DIČ: CZ65410777 +420 261 217 774
triangel@triangel.cz
WWW.TRIANGEL.cz

Complete supply of ventilated facades











