

The cladding tiles are made of bricks (= fair-faced brickwork) in the crosswise format consisting of a front slab and a rear slab connected with ribs (between the longitudinal openings). MOEDING® tiles are divided into two groups according to the length: MOEDING® Alpahton and MOEDING® Longoton.

## MOEDING® Alpahton – tile length up to 1500 mm

### 1) COLOR

The clay tiles MOEDING® Alpahton are available in **18 standard ceramic colors**. Special colors and special surfaces are possible on request.

blue grey	turquoise			
pearl grey	quartz grey	iron grey	vulcano grey	
ivory	beige	light grey		
salmon	pastel red	natural red	orange	
oxide red	dark red	brown		
sand	saffron			

### 2) FORMATS

- **The height** of Alpahton tiles is from 150–400 mm (axial dimension). Vertical scaling by 12.5 mm up to 300 mm; from 300mm by 25 mm different heights on request for the need of special tooling.
- **The length** of Alpahton tiles is from 150–1500 mm (axial dimension). Horizontal scaling by 1 mm.
- **The thickness** of Alpahton tiles is 30 mm.

## MOEDING® Longoton – tile length up to 3000 mm

### 1) COLOR

The clay tiles MOEDING® Longoton are available in **16 basic ceramic colors**. Special colors and special surfaces are possible on request.



### 2) FORMATS

- **The height** of Longoton tiles is from 150 – 1000 mm (axial dimension).  
Vertical scaling by 50 mm.
- **The length** of Longoton tiles is from 150 – 3000 mm (axial dimension).  
Horizontal scaling by 1 mm.
- **The thickness** of Longoton tiles is 40 mm.

### 3) SURFACE (Alphaton + Longoton)

1. Patinated
2. Deep grooved
3. Waved
4. Polished
5. Standard
6. Lamella
7. Grooved
8. Brushed
9. Glazed - glossy and matt



## Special shapes of brick tiles

### Baguette

An interesting design element of the facades is Baguette.

A complementary design element for the facade part, it is used for shielding the windows, covering ventilation or air conditioning and other purposes.

The standard cross section is 50 x 50 mm and maximum length is up to 1500 mm.



### Lamella

A flat shaped facade element for shielding the windows. Lamella may be used both horizontally and vertically. Maximum length of a lamella is 5000 mm.



## 4) Way of fixing and details

MOEDING allows horizontal and vertical installation.

### Wild joint-cut

1. Cladding tile
2. Rapid clip
3. horizontal profile – Gen 06
4. Join profile
5. Anchor
6. Thermal insulation
7. Air space



### Standard joint-cut

1. Cladding tile
2. Rapid clip
3. horizontal profile – Gen 06
4. Join profile
5. Anchor
6. Thermal insulation
7. Air space



Rapid clip makes exchange of the tiles on facade easier.



## 5) FLAMMABILITY

According to CSN 73 0810/ 2016: A1

*For more information contact Triangel company.*

Triangel spol. s r.o.  
Černokostelecká 2085/24  
100 00 Praha 10  
Czech Republic

IČO: 65410777, DIČ: CZ65410777

+420 261 217 774  
trangel@triangel.cz  
WWW.TRIANGEL.CZ

**Complete supply  
of ventilated facades**